


35 x 7 Non-Rotating/Compacted



Nominal Diameter		Weight 100m	Minimum Breaking Load 2,160 N/mm ²	
Mm	Kg		kN	kg
10	48	96	9,800	
11	58	116	11,800	
12	68	138	14,100	
13	81	162	16,500	
14	94	188	19,200	
15	108	216	22,000	
16	122	245	25,000	
17	138	277	28,200	
18	155	311	31,700	
19	173	346	35,300	
20	195	372	37,900	
21	215	424	43,200	
22	241	474	48,300	
23	267	519	52,800	
24	284	551	56,100	
25	312	606	61,800	
26	335	652	66,400	
27	360	700	71,300	
28	391	760	77,400	
29	413	803	81,800	
30	446	866	88,200	
31	478	929	94,600	
32	503	977	99,500	
33	536	1,032	105,000	
34	574	1,105	113,000	
35	606	1,166	119,000	
36	642	1,235	126,000	
37	674	1,296	132,000	
38	718	1,381	141,000	
39	753	1,449	148,000	
40	793	1,525	155,000	
41	828	1,594	162,000	
42	870	1,673	170,000	
43	913	1,756	179,000	
44	948	1,825	190,000	
45	993	1,912	195,000	
46	1,040	2,007	207,000	
47	1,080	2,086	212,000	
48	1,140	2,186	223,000	