



6 x 36 WS + IWRC

Minimum breaking force factor: 0.356

Nominal rope length mass factor: 0.409

Nominal Diameter	Weight 100m	Minimum Breaking Load 1,960 N/mm ²	
		kN	kg
8	26.20	44.70	4,560
9	33.10	56.50	5,760
10	40.90	69.80	7,120
11	49.50	84.40	8,600
12	58.90	100.00	10,200
13	69.10	118.00	12,000
14	80.20	137.00	14,000
16	105.00	179.00	18,300
18	133.00	226.00	23,000
19	148.00	252.00	25,700
20	164.00	279.00	28,500
22	198.00	338.00	34,500
24	236.00	402.00	41,000
26	276.00	472.00	48,100
28	321.00	547.00	55,800
30	368.00	628.00	64,000
32	419.00	715.00	72,900
34	473.00	807.00	82,300
36	530.00	904.00	92,200
38	591.00	1,010.00	103,000
40	654.00	1,120.00	114,000
42	721.00	1,230.00	125,000
44	792.00	1,350.00	138,000
48	942.00	1,610.00	164,000
51	1,064.00	1,815.00	185,000
52	1,110.00	1,890.00	193,000
56	1,280.00	2,190.00	223,000
57	1,329.00	2,267.00	231,000
60	1,470.00	2,510.00	256,000
64	1,675.00	2,858.00	291,000