

## Goldstrand Fibre Rope

Goldstrand has established itself as a leading brand in the marine and dredging industry.

With full stock available from 32mm up to 80mm, Goldstrand is manufactured to the highest standards to produce excellent performance in the most demanding conditions. This is a cost effective Super Strength Rope, with excellent abrasion resistance, ensuring a long life-time.

### PROPERTIES

- Material: Goldstrand Polyolefin Yarns
- Specific Gravity: 0.94 (Float)
- Melting Point: 165
- Water Absorption: None
- Abrasion Resistance: Excellent.

### APPLICATIONS

Mooring Lines, Towing Lines, Anchor Lines Specs.



Lloyds Register Certification available on request



### 8 STRAND SPECIFICATION

DIA (mm)	WEIGHT (Kg/200m)	TENSILE STRENGTH (Ton)
24	57.6	10.9
28	78.8	14.5
32	102.2	17.9
36	128.2	22.0
40	158	29.7
42	177	30.9
45	204	35.4
48	229	41.3
50	249	42.5
52	268	46.0
56	312	53.2
60	358	60.5
64	407	68.2
72	516	84.0
75	559	93.0
80	638	105.6
85	721	118.8
90	807	133.4
95	899	146.5
100	996	162.4
105	1,098	179.0
110	1,205	196.5
115	1,317	214.0
120	1,436	233.8